



BR67S  
LAND

BR67UW  
UNDERWATER



**SPECIFICATIONS**

|                    |   |
|--------------------|---|
| MAX. OUTPUT        | 1400 bpm                                |
| FLOW RANGE         | 26 – 34 lpm                             |
| PRESSURE           | 105 – 140 bar (2000 psi)                |
| MAX. BACK PRESSURE | 17 bar (250 psi)                        |
| OPTIMUM FLOW       | 30 lpm                                  |
| SYSTEM TYPE        | Open Centre                             |
| PORTING            | -8 SAE O-Ring                           |
| HOSE WHIPS         | 18" Long                                |
| HYD CONNECTION     | Flat Face Couplings                     |
| WIDTH              | 46cm BR6717801A<br>41cm BR67320/33201   |
| LENGTH             | 73cm BR6717801A<br>68cm BR67320/33201   |
| WEIGHT             | 34 kg BR6717801A<br>30 kg BR67320/33201 |

**STEEL CAPACITY**

|                         |                          |
|-------------------------|--------------------------|
| BR6717801A<br>BR6733201 | 1-1/4" Hex x 6-1/4 Shank |
| BR67320                 | 1-1/8" Hex x 6-1/4 Shank |

**Features and Benefits**

Stanley's line of handheld breakers is the largest in the world, with a wide selection of models suited to virtually any application.

The **BR67** is a medium-duty tool for work in the 70-90 pound class. They are highly productive in utility construction, street maintenance, repair of water and gas mains, and general contracting jobs.

This breaker is available in both an Anti-Vibration Handle (**BR67S**) and T-Handle (**BR67UW**) Model.

The **BR67S** has Sprung-Isolated Anti-Vibration Handles which greatly reduce operator fatigue, literally allowing the breaker to float

in the user's hands. Built in Handle Stops allow the operator to apply full body weight in tough applications. All **BR67S** breakers come equipped with a safety trigger lock system to prevent accidental activation of the tool.

The Easi-Ride™ foot, fitted to the **BR67S**, absorbs and controls tool-bit bounce, greatly reducing operator fatigue.

Feathering On/Off Valve allows the operator to control the output energy of the tool through the full range from 0 to 1400 blows per minute, making start-up and initial tool placement easy.

Diaphragm-Type Accumulator design provides ease of maintenance and extended service life of the tool. All models operate at a maximum back pressure of 17 bar (250 psi) on open-centre systems.

Accumulator on **BR67S** can be serviced without disassembling the tool. Both models operate on open centre systems and are available in 1-1/4 in. chuck hex sizes.

The **BR67UW** breaker is designed for use underwater.

A complete line of steels for breaking, cutting or driving are also available.

## ORDERING INFORMATION

| MODEL/PART No. | DESCRIPTION   |
|----------------|---|
| BR6717801A     | LAND MODEL<br>Anti-Vibration Handle Breaker, 1-1/4 in. hex x 6-1/4 in. shank, Easi-Ride Foot Assy, 26-34l pm hydraulic flow rate, Hose Whips & Couplings, Safety Trigger Lock |
| BR67320        | UNDERWATER MODEL<br>T-Handle Breaker, 1-1/8 in. hex x 6-1/4 in. shank, 26-34 lpm hydraulic flow rate, Hose Whips & Couplings  |
| BR6733201      | UNDERWATER MODEL<br>T-Handle Breaker, 1-1/4 in. hex x 6-1/4 in. shank, 26-34 lpm hydraulic flow rate, Hose Whips & Couplings  |

## ACCESSORIES

| PART No. | DESCRIPTION  |
|----------|--|
| MP38032  | Moil Point, 15 in. B/C                                   |
| MP45032  | Moil Point, 18 in. B/C                                   |
| NC38032  | Narrow Chisel 1 in. Blade, 15 in. B/C                    |
| NC45032  | Narrow Chisel 1 in. Blade, 18 in. B/C                    |
| BC38032  | Broad Chisel 3 in. Blade, 15 in. B/C                     |
| BC45032  | Broad Chisel 3 in. Blade, 18 in. B/C                     |
| AC33032  | Asphalt Cutter 5 x 6 in. Blade, 13 in. B/C (Curved Edge) |
| TC28032  | Tarmac/Deltic Cutter 4.5 x 5 in. Blade, 11 in. B/C       |
| DS35032  | Digger Spade 5 x 8 in. Blade, 14 in. B/C                 |
| CS38032  | Clay Spade 5.5 x 8 in. Blade, 15 in. B/C                 |
| TSL23032 | Tamper Stem (Large Taper), 9 in. B/C                     |
| TPL125R  | Tamper Pad (Large Bore), 125mm Dia                       |
| TPL180R  | Tamper Pad (Large Bore), 180mm Dia                       |
| TPL160S  | Tamper Pad (Large Bore), 160mm Square                    |

1-1/4 in. hex x 6-1/4 in. shank chisels

## WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

## SERVICE ITEMS / TOOLS

| PART No. | DESCRIPTION            |
|----------|------------------------|
| 04596    | Seal Kit (Both models) |
| 04337    | O-Ring Tool Kit        |

## TEST EQUIPMENT

|         |                        |
|---------|------------------------|
| 02835   | Accumulator Tester     |
| BCHA/1B | Charging Hose Kit      |
| 5007    | Charging Connector     |
| 04182   | Flow & Pressure Tester |

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult us.